

Breitflanschträger

Grenzabmaße und Formtoleranzen DIN 1025-2, EN 10034

Werkslängen:

S235JR ab HEA 200 / HEB 200 / HEM 160 bis 24,2 m lagernd

S355J2 bis 18,1 m lagernd

Andere Qualitäten auf Anfrage

S235JR / EN 10025

Abmessungen	HEB (IPB)	HEA (IPBL)	HEM (IPBV)
100	✓	✓	✓
120	✓	✓	✓
140	✓	✓	✓
160	✓	✓	✓
180	✓	✓	✓
200	✓	✓	✓
220	✓	✓	✓
240	✓	✓	✓
260	✓	✓	✓
280	✓	✓	✓
300	✓	✓	✓
320	✓	✓	*
340	✓	✓	*
360	✓	✓	*
400	✓	✓	*
450	✓	✓	*
500	✓	✓	*
550	✓	✓	*
600	✓	✓	*
650	*	*	*
700	*	*	*
800	*	*	*
900	*	*	*
1000	*	*	*

S355J2 / EN 10025

Abmessungen	HEB (IPB)	HEA (IPBL)
100	✓	✓
120	✓	✓
140	✓	✓
160	✓	✓
180	✓	✓
200	✓	✓
220	✓	✓
240	✓	✓
260	✓	✓
280	✓	✓
300	✓	✓
320	*	*
340	*	*
360	*	*
400	✓	✓

Restliche Abmessungen in S355J2 auf Anfrage beschaffbar

✓ = lagernd

* = auf Anfrage